





## **XH SERIES**

HIGH-VOLTAGE LITHIUM BATTERY FORKLIFT

With capacity of 28,000 to 35,000kg

### HANGCHA GROUP CO., LTD.

Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.



IS045001:2018



IS014001:2015





YouTube

IS09001:2015



Forklift" App

2023 VERSION 1/COPYRIGHT 2023/12



### XH SERIES HIGH-VOLTAGE LITHIUM BATTERY FORKLIFT

Your reliable, powerful and connected working machine.

Independently developed by Hangcha on the basis of decades of deep understanding of electric forklifts and internal combustion forklifts, XH series high-voltage counterweight lithium battery forklifts are a new series of high-voltage counterweight lithium battery forklifts that first use a new energy vehicle voltage platform and represent a breakthrough over the traditional design concept. Representing a redefinition of electric forklifts in terms of efficiency, power, reliability, etc.,

XH series forklift models have performance and operating condition completely superseding that of the internal combustion forklifts.



## FASTER EFFICIENCY

Through disruptive battery and fast charging technology, the charging time is greatly shortened.

Fast charging makes it possible for the whole vehicle to work continuously, shortening the waiting time and greatly improving efficiency.

**4000** »

Under normal charging and discharging conditions, the lithium battery of Hangcha products has a

the lithium battery of Hangcha products has a capacity retention rate of more than 75% and a life span of up to 10 years after 4000 cycles of charging and discharging.

HIGH-VOLTAGE

282kWh

FOR YOUR BUSINESS

# A PERFECT COMBINATION

With the inherited exterior design of X series internal combustion forklifts and a smooth and sturdy profile, the whole vehicle is stylish, sturdy and powerful, showing modern industrial aesthetics.






### **ADVANCEMENT**

A high-torque permanent magnet synchronous motor provides strong power for the vehicle with performance indicators benchmarked against that of internal combustion forklifts.

#### Travel speed (km/h)



### Max. gradeability(%)







- A 618V high-voltage platform with low system loss, a standard chilled water tank for heavy-duty truck to achieve good heat dissipation.
- With motor, electric control and battery adopting liquid-cooling heat dissipation, the forklift can absolutely carry out long-time and high-intensity operations as internal combustion forklifts.



The vehicle has independently developed VCU program along with PDU+MCU+BMS+DC/DC to form a reliable and efficient drive system with flexible function configuration.





- Both the battery and junction box have MSD(Manual Service Disconnect) maintenance switches to enable one-click power-down and safer maintenance.
- The high-voltage lithium battery is equipped with an automatic fire extinguisher for the standard configuration. The vehicle is equipped with a pipe network automatic fire extinguisher for the standard configuration.









- The electrical system has high-voltage interlocking, insulation monitoring and potential balancing functions to offer vehicle-grade safety.
- Key structural parts have been verified highly reliable by the market for many years while being used by internal combustion forklifts.



- The overturnable cab and electric tipping cylinder make tipping easier and more labor-saving.
- The wide-opened hood and removable cover better facilitate repair and maintenance of electrical components.







### Features

Transmission	Standard	Options
Pneumatic tyre	•	
Solid tyre		0
Steering system		
Fully hydraulic power steering	•	
Centralized lubrication system (machine)		0
Truck		
Tow pin	•	
Electrostatic discharge chain	•	
Rear-view mirror on right & left mudguards	•	
Operating system		
Integrated joystick	•	
Adjustable steering column	•	
Adjustable armrest	•	
	•	
Hydraulic system		
Variable hydraulic pump system	•	_
Four-way hydraulic valve		0
Operation proportion control	•	
Cab		
Cabin	•	
Climate control system (air-conditioning and heater)	•	
Manual tilting cabin	•	
Electric tilting cabin	•	
Radio	•	
Sunshade	•	
USB charging interface	•	
Clothes hanger hook	•	
Reading light	•	
1 x 24V power supply		0
1 x 12V power supply		0
License plate frame		0
Fan	•	
Lifting components		
Duplex mast	•	
Standard lifting height	•	
Optional lifting height		0
Standard fork	•	
Other fork specifications		0
Fork hook on type		0
Hydraulic Fork Positioning	•	_
Independently-adjustable fork		0
Built in Sideshift	•	
Other		
Standard color	•	
User defined colour		0
Vehicle toolkit	•	

Electrical System	Standard	Options
Operator Presense System (OPS) with buzzer	•	
LCD display screen	•	
Main power switch	•	
Emergency power off switch	•	
Maintenance-free 24V lead acid battery	•	
Reverse buzzer	•	
High decible horn	•	
LED lights (entire vehicle)	•	
2 x Working light on front mudguard	•	
2 x Front working light on top of cabin	•	
2 x Rear working light on top of cabin	•	
2 x Working light on both sides of mast	•	
Reverse sensor	•	
Rearview camera system	•	
Rearview camera system with memory		0
Front & rearview camera system		0
Front & rearview camera system with memory		0
4 directions camera system with single display		0
4 directions camera recording system with single display		0
In cabin CCTV		0
Rear blue safety light		0
Front and rear blue safety light		0
Three sided blue danger zone light		0
Overspeed alarm		0
Speed limitation		0
Voice reverse alarm		0
Automatic fire suppression system	•	
Automatic fire suppression system for lithium battery pack	•	
Two-way radio		0
Weight indicator in display	_	0
Flashing warning light (non rotating) with control switch	•	
Tyre pressure monitoring		0
On-board diagnostics system	•	
Water cooling system for lithium battery	•	
Manual Service Disconnect (MSD) switch	•	
High voltage interlock	•	
Insulation protection	•	
Power-on self-test	•	
Energy recovery (braking regeneration)	•	
Vehicle Control Unit (VCU)	•	
Dual charging ports	•	
Turning deceleration		0
Hour meter	•	
Battery charge indicator	•	
Low hydraulic pressure alarm indicator	•	
Hydraulic oil filter warning indicator	•	
Drive mode indicator	•	·
Parking brake indicator	•	
Service indicator	•	